

View Online at <https://aerobasegroup.com/nsn/5962-01-497-8147>

**Maximum Power Dissipation Rating:**

889.0 milliwatts

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Storage Temperature Range:**

-65.0/+160.0 degrees celsius

**Features Provided:**

Monolithic and electrostatic sensitive and hermetically sealed

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Design Function And Quantity:**

1 converter, digital to analog

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit-octal 8-bit serial d/a conerter

**Voltage Rating And Type Per Characteristic:**

20.0 volts power source

**Special Features:**

Max528cpp operates from a single supply up to 15 volts or from split supplies totaling up to 20 volts, including +5v/-15v, +12v/-5v, and +15v/-5v.

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0