NSN 5962-01-498-8776

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-498-8776

| Outside a Transporture Brown |
|--|
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| End Application: |
| Kok-22/22a |
| Features Provided: |
| Electrostatic sensitive and inverted output and high speed |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Hex 1 input |
| Criticality Code Justification: |
| Cbbl |
| Design Function And Quantity: |
| 6 schmitt trigger |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| I.C. |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Special Features: |
| Cmos logic; balanced propagation delay and transition times; unlimited input rise and fall times |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |