NSN 5962-01-500-9547

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-500-9547

1.5 waits Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	1.5 watts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Operating Tempurature Range:
Features Provided: Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	-55.0/+125.0 degrees celsius
Features Provided: Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Storage Tempurature Range:
Electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	-65.0/+150.0 degrees celsius
Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Features Provided:
Ceramic Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Electrostatic sensitive and monolithic
Inclosure Configuration: Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Material:
Leadless flat pack Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Ceramic
Product Name: Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Configuration:
Microcircuit programmable array logic Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Leadless flat pack
Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Product Name:
-0.5 volts input and 7.0 volts input Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Microcircuit programmable array logic
Memory Device Type: Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Voltage Rating And Type Per Characteristic:
Pal Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	-0.5 volts input and 7.0 volts input
Special Features: Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Memory Device Type:
Altered item/made with smd 5962-89839 Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Pal
Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Altered item/made with smd 5962-89839
Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:	$96906 \hbox{-mil-std-}883 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	20 leadless
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
	Demilitarization:
Yes - demil/mli	Yes - demil/mli
Fiig:	Fiig:
A458a0	A458a0