## NSN 5962-01-502-3760

Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-502-3760

Maximum Power Dissipation Rating:
35.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Nuclear power plants
Features Provided:
Electrostatic sensitive
Inclosure Configuration:
Flat pack
Design Function And Quantity:
1 converter, dc
Terminal Surface Treatment:
Gold
Product Name:
Microcircuit, hybrid, linear, 5 volt, single output with integral emi filter, dc/dc converter
Voltage Rating And Type Per Characteristic:
-0.5 volts input and 50.5 volts input
Hybrid Technology Type:
Monolithic
Special Features:
Generic p/n 34031
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
$96906 \hbox{-mil-std-}883 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$
Terminal Type And Quantity:
17 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0