## NSN 5962-01-502-5587

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-502-5587

| Maximum Power Dissipation Rating:                    |
|--|
| 1.25 watts   |
| Operating Tempurature Range:                         |
| -40.0/+85.0 degrees celsius                          |
| Storage Tempurature Range:                           |
| -65.0/+150.0 degrees celsius                         |
| Features Provided:                                   |
| Electrostatic sensitive                              |
| Inclosure Material:                                  |
| Plastic  |
| Inclosure Configuration:                             |
| Dual-in-line   |
| Output Logic Form:                                   |
| Bipolar metal-oxide semiconductor                    |
| Design Function And Quantity:                        |
| 4 buffer, tri-state                                  |
| Terminal Surface Treatment:                          |
| Solder   |
| Product Name:  |
| 3.3-v abt quadruple bus buffers with 3-state outputs |
| Voltage Rating And Type Per Characteristic:          |
| -0.5 volts input and 7.0 volts input                 |
| Terminal Type And Quantity:                          |
| 14 printed circuit                                   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A458a0   |
|  |
|  |