# NSN 5962-01-502-9848

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-502-9848

# Maximum Power Dissipation Rating:

900.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **End Application:**

Striker fighting vehicle

# **Features Provided:**

Electrostatic sensitive and monolithic

#### **Inclosure Material:**

Glass and ceramic

#### Inclosure Configuration:

Dual-in-line

#### **Design Function And Quantity:**

# 1 switch, analog

#### **Terminal Surface Treatment:**

Solder

# **Product Name:**

Microcircuit, linear, analog switch, spst, 4-channel, monolithic silicon

# Voltage Rating And Type Per Characteristic:

25.0 volts input

# **Special Features:**

Generic p/n dg442a

# **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0