NSN 5962-01-505-2974

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-505-2974

# Maximum Power Dissipation Rating:

1.2 watts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **End Application:**

MISS-IL-E,P-ATRI

### **Features Provided:**

Electrostatic sensitive and monolithic

### **Inclosure Material:**

Glass and ceramic

### Inclosure Configuration:

Dual-in-line

## Product Name:

Microcircuit, digital fused pal

## Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

# Time Rating Per Chacteristic:

25.00 nanoseconds access

## Memory Device Type:

Pal

### **Special Features:**

Altered item made with smd 5962-8867001la (generic number c22v10)

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

24 printed circuit

### Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0