

View Online at <https://aerobasegroup.com/nsn/5962-01-506-0115>

Body Length:

Between 12.400 millimeters and 12.600 millimeters

Body Width:

Between 6.000 millimeters and 6.200 millimeters

Body Height:

Between 0.850 millimeters and 6.200 millimeters

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

4920-01-495-9100, test station f16-c/d

Features Provided:

Electrostatic sensitive

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Quad 5 input

Design Function And Quantity:

1 driver, line

Product Name:

Microcircuit, digital, fast cmos, 16-bit noninverting buffer/line driver with series resistor and three-state outputs, ttl compatible inputs and limited output voltage swing

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Capitance Rating Per Characteristic:

6.00 input picofarads and 8.00 output picofarads

Time Rating Per Characteristic:

1.50 nanoseconds propagation delay and 4.80 nanoseconds propagation delay

Terminal Type And Quantity:

48 gullwing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0