NSN 5962-01-506-3323

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-506-3323 **Body Length:** 1.000 inches **Body Width:** 1.000 inches **Body Height:** 0.450 inches **Maximum Power Dissipation Rating:** 10.0 watts **Operating Tempurature Range:** -40.0/+70.0 degrees celsius Storage Tempurature Range: -40.0/+105.0 degrees celsius **End Application:** F16C-/D-AVI-ONIC **Features Provided:** Electrostatic sensitive **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 1 converter, dc **Current Rating Per Characteristic:** 3.00 amperes forward current, peak total value not applicable and 10.00 milliamperes forward current, nonrepetitive, peak total value blank **Terminal Surface Treatment:** Solder **Product Name:** Non-isolated, 5v to 3.3v, 3a dc/dc converter **Voltage Rating And Type Per Characteristic:** 7.0 volts absolute input and 4.75 volts power source and 5.5 volts power source and 3.3 volts output **Hybrid Technology Type:** Multichip **Special Features:** Logic input controlled on/off (ttl high=on), 200khz switching freq. **Terminal Type And Quantity:** 6 pin Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-506-3323

Hybrid Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0