NSN 5962-01-506-3720

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-506-3720

Body Length:
0.705 inches
Body Width:
0.295 inches
Body Height:
0.098 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
89954/114e6472g1
Features Provided:
Electrostatic sensitive
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
nput Circuit Pattern:
4 input
Criticality Code Justification:
Cbbl
Design Function And Quantity:
14 clock, logic
Case Outline Source And Designator:
Ms-013ae joint electron device engineering council
Product Name:
Microcircuit, digital, plastic encapsulated (surface mount)procurement andselection requirements
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source and 2.4 volts high level output and 0.4 volts low level output
Special Features:
Clock synthesizer/driver, maximum digital input voltage is supply voltage plus 0.5v, supply voltages +3.3v or +5.0v, multiple clock outputs
meet requirements ofmost pentium motherboards
Special Test Features:
Approved pem test facilities: pikes peak test labs, inc. And amkor test services, wichita, ks.
Terminal Type And Quantity:
28 gullwing
Specification Data:
39954-356a1407 manufacturers specification

N/a

Shelf Life:

NSN 5962-01-506-3720

Digital Microcircuit - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0