## NSN 5962-01-509-4946

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-509-4946

View Online at https://aerobasegroup.com/nsn/5962-01-509-4946
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Nha circuit card i/o processor pn 114040-xxx cage 09344, f-15 hud
Features Provided:
Electrostatic sensitive and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Terminal Surface Treatment:
Solder
Product Name:
Composite test video, horizontal decode
Voltage Rating And Type Per Characteristic:
-0.5 volts input and 7.0 volts input
Time Rating Per Chacteristic:
25.00 nanoseconds access
Memory Device Type:
Pal
Special Features:
Recommended operating supply voltage (vcc) 4.5 to 5.5 vdc
Supplementary Features:
Made from 22-input, 10-output, ee cmos programmable and-or array logic pn 5962-8984104la cage 67268
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0