## NSN 5962-01-512-1280

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-512-1280

Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
C-17a, arc 169 solid
Features Provided:
Electrostatic sensitive and high precision and wideband
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
3 input
Criticality Code Justification:
Cbbl
Design Function And Quantity:
1 multiplier, analog
Case Outline Source And Designator:
Pdso-g8 joint electron device engineering council
Current Rating Per Characteristic:
1000.00 milliamperes reverse current, dc microamperes and 1000.00 microamperes average forward current averaged over a full 60-hz
cycle not applicable and 1.00 microamperes collector cutoff current, dc, base open not applicable
Voltage Rating And Type Per Characteristic:
-22.0 volts power source and -15.0 volts power source
Special Features:
The inclosure configuration (mrc cqsz) is an 8-lead soic not a dip, but there is no correct code for that pkg
Terminal Type And Quantity:
8 gullwing
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0