## NSN 5962-01-512-3858

Linear Microcircuit - Page 1 of 1

**Fiig:** A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-512-3858

Body Length:
Between 0.370 inches and 0.380 inches
Body Width:
Between 0.150 inches and 0.157 inches
Body Height:
Between 0.045 inches and 0.064 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Nha pn 61-41853-001 cage 00724, component of pn 03-07521-001 cage 00724, used in amplifier radio frequency 5996-01-494-7957, e/i
e-3 sentry aircraft
Features Provided:
Electrostatic sensitive
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Design Function And Quantity:
1 driver, high current
Current Rating Per Characteristic:
12.00 amperes average forward current averaged over a full 60-hz cycle not applicable
Product Name:
12a-peak low-side mosfet driver, bipolar/cmos/dmos process
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Time Rating Per Chacteristic:
23.00 nanoseconds rise transient and 30.00 nanoseconds fall
Special Features:
Bicmos/dmos construction, inverting driver
Terminal Type And Quantity:
8 gullwing
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli