NSN 5962-01-512-8813

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-512-8813 **Overall Height:** 0.069 inches **Body Length:** 0.344 inches **Body Width:** 0.157 inches **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **End Application:** Arc 169 solid **Features Provided:** Electrostatic sensitive and low power **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Hex 1 input **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 6 schmitt trigger **Case Outline Source And Designator:** Ms-120 joint electron device engineering council **Product Name:** Hex schmitt trigger **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source and -0.5 volts input and 7.0 volts input **Capitance Rating Per Characteristic:** 2.00 input picofarads **Time Rating Per Chacteristic:** 1.00 nanoseconds propagation delay and 9.00 nanoseconds propagation delay **Special Features:** Jitter free outputs from slowly changing inputs; silicon **Terminal Type And Quantity:** 14 gullwing Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-512-8813

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0