Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-512-8813

# **Overall Height:**

0.069 inches

#### **Body Length:**

0.344 inches

## Body Width:

0.157 inches

#### **Operating Tempurature Range:**

-40.0/+85.0 degrees celsius

#### **End Application:**

Arc 169 solid

#### Features Provided:

Electrostatic sensitive and low power

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

Hex 1 input

#### Criticality Code Justification:

Cbbl

#### **Design Function And Quantity:**

6 schmitt trigger

## Case Outline Source And Designator:

Ms-120 joint electron device engineering council

#### **Product Name:**

Hex schmitt trigger

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source and -0.5 volts input and 7.0 volts input

## Capitance Rating Per Characteristic:

2.00 input picofarads

#### **Time Rating Per Chacteristic:**

1.00 nanoseconds propagation delay and 9.00 nanoseconds propagation delay

#### **Special Features:**

Jitter free outputs from slowly changing inputs; silicon

#### **Terminal Type And Quantity:**

14 gullwing

### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5962-01-512-8813

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

