NSN 5962-01-513-0830

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-513-0830 **Overall Height:** 1.20 millimeters **Body Length:** 5.10 millimeters **Body Width:** 4.50 millimeters **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **End Application:** Arc 169 solid **Features Provided:** Electrostatic sensitive and high performance and high speed and w/enable **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Dual 3 input **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 2 decoder, two to four line **Case Outline Source And Designator:** -0-153 joint electron device engineering council **Product Name:** Dual 2-line to 4-line decoder/demultiplexer **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source and -0.5 volts input and 7.0 volts input **Time Rating Per Chacteristic:** 6.50 nanoseconds propagation delay time, high to low level output and 6.50 nanoseconds propagation delay time, low to high level output **Special Features:** The active low-enable input can be used as a data input line in demultiplexing operations; fully buffered inputs. **Terminal Type And Quantity:** 16 gullwing Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-513-0830

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0