NSN 5962-01-513-2163

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-513-2163

Body Length:
0.405 inches
Body Width:
Between 0.220 inches and 0.310 inches
Maximum Power Dissipation Rating:
730.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
F-15e hud wfov
Features Provided:
Electrostatic sensitive and high slew rate and high speed and high current
Inclosure Material:
Ceramic or glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
2 input
Criticality Code Justification:
Cbbl
Design Function And Quantity:
1 amplifier, video
Product Name:
Product Name: High speed, high output current, voltage feedback amplifi
High speed, high output current, voltage feedback amplifi
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard Shelf Life:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard Shelf Life: N/a
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard Shelf Life: N/a
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard Shelf Life: N/a Unit Of Measure:
High speed, high output current, voltage feedback amplifi Voltage Rating And Type Per Characteristic: 36.0 volts total supply Special Features: 170 mhz unity gain bandwidth Terminal Type And Quantity: 8 printed circuit Specification Data: 67268-5962-95536 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: