# NSN 5962-01-513-8357

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-513-8357

## **Body Length:**

Between 0.920 inches and 1.060 inches

# Body Width:

Between 0.220 inches and 0.310 inches

## **Body Height:**

Between 0.070 inches and 0.185 inches

## **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## End Application:

F16 aircraft

#### Features Provided:

Static operation and electrostatic sensitive and w/enable and high speed

#### Inclosure Material:

Ceramic

## Inclosure Configuration:

Dual-in-line

# Output Logic Form:

Complementary-metal oxide-semiconductor logic

# Input Circuit Pattern:

18 input

## **Current Rating Per Characteristic:**

120.00 milliamperes reverse current, dc absolute

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## Capitance Rating Per Characteristic:

5.00 input picofarads and 7.00 output picofarads

## **Time Rating Per Chacteristic:**

45.00 nanoseconds access

#### Memory Device Type:

Ram

## Memory Capacity:

16k, 4k x 4

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

24 printed circuit

# NSN 5962-01-513-8357

Memory Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

