NSN 5962-01-514-7917

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-514-7917

| Operating Tempurature Range: |
|--|
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and programmable |
| Inclosure Material: |
| Glass and ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 22 input |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Mircrocircuit, digital fused pal |
| Voltage Rating And Type Per Characteristic: |
| -2.0 volts input and 7.0 volts input |
| Time Rating Per Chacteristic: |
| 25.00 nanoseconds access |
| Memory Device Type: |
| Pal |
| Special Features: |
| Altered drawing, generic number c22v10, burn file p/nbf11472227-87, burn file file name: 22787.Fwv, data checksum 41d8 |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |