NSN 5962-01-515-8049

Digital Microcircuit - Page 1 of 1

500.00 nanoseconds delay

Supplementary Features:

Terminal Type And Quantity:

Manual reset input and complementary active-high reset

Precision monitoring of 2.5v, 3v, 3.3v and 5v power supplies; reset threshold 4.38 v

Special Features:

5 gullwing

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

No Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-515-8049 **Body Length:** Between 2.80 millimeters and 3.00 millimeters **Body Width:** Between 1.50 millimeters and 1.75 millimeters **Body Height:** Between 0.90 millimeters and 1.30 millimeters **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Bipolar metal-oxide semiconductor **Design Function And Quantity:** 1 monitor **Case Outline Source And Designator:** -0178 joint electron device engineering council **Current Rating Per Characteristic:** 3.00 microamperes collector cutoff current, dc, with specified resistance between base and emitter absolute and 8.00 microamperes reverse current, dc absolute **Product Name:** Microprocessor supervisory circuits Voltage Rating And Type Per Characteristic: 4.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:**