NSN 5962-01-518-9970

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-518-9970

Body Length:
1.141 inches
Body Width:
0.400 inches
Body Height:
0.097 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
C-17a acft
Features Provided:
Electrostatic sensitive and high speed
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Criticality Code Justification:
Cbbl
Current Rating Per Characteristic:
65.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, plastic encapsulated, 256k x 16 bit high speed static ra (5.0v operating)
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
8.00 input picofarads and 6.00 output picofarads
Time Rating Per Chacteristic:
10.00 nanoseconds access
Memory Device Type:
Ram
Memory Capacity:
256k x 16
Special Features:
Ttl compatable inputs & outputs, three state outputs
Consolina Total Foothises

Special Test Features:

Upscreening testing consisting of extended temperature range testing

NSN 5962-01-518-9970

Memory Microcircuit - Page 2 of 2



Test Data Document:

89954-356a1407 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Termina	l Type A	and Quant	ity
---------	----------	-----------	-----

44 j-hook

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A458a0