## NSN 5962-01-520-3143

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-520-3143 **Body Length:** 0.295 inches **Body Width:** 0.212 inches **Body Height:** 0.070 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** C-17a **Features Provided:** Electrostatic sensitive and low power and high speed and selected item **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input and quad 3 input **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 4 switch, single pole double throw **Product Name:** Microcircuit, plastic encapsulated (surface mount - procurement and selection requirements (for analog switch) Voltage Rating And Type Per Characteristic: 44.0 volts total supply **Special Features:** Low On-resistance, break before make, analog signal range extends to supply voltage rails **Special Test Features:** Adg333absr is 100 percent upscreened per para 3.1.1 of dwg 89954/356a1407 by approved test facility for operation intemperatures of -55c to +125c. **Test Data Document:** 89954-356a1407 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 20 gullwing Shelf Life: N/a **Unit Of Measure:** 

Fiig: A458a0

No

**Demilitarization:**