NSN 5962-01-520-4953

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-520-4953

Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Eurofighter 2000 Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Eurofighter 2000 Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
End Application: Eurofighter 2000 Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
End Application: Eurofighter 2000 Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Eurofighter 2000 Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Inclosure Material: Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Ceramic Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Output Logic Form: Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Transistor-transistor logic Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Design Function And Quantity: 1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
1 buffer Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Product Name: 16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
16 bit buffers/drives with 3 state outputs Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
Voltage Rating And Type Per Characteristic: -0.50 volts total supply and 7.0 volts total supply	
-0.50 volts total supply and 7.0 volts total supply	
Special Features:	
380 military fine pitch ceramic flat	
Test Data Document:	
67268-5962-94587 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawir	ıg,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 96906-mil-std-8	383
standard (includes industry or association standards, individual manufactureer standards, etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	