NSN 5962-01-527-5529

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-527-5529 |
|---|
| Operating Tempurature Range: |
| -55.0/+150.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| End Application: |
| Nsn: 5895-01-277-4802; radio set. |
| Design Function And Quantity: |
| 4 switch |
| Current Rating Per Characteristic: |
| 1.50 amperes forward current, peak total value not applicable |
| Product Name: |
| Microcircuit, linear, quad darlington switch. |
| Voltage Rating And Type Per Characteristic: |
| 30.0 volts input |
| Special Features: |
| Specification establishing detailed requirements for a class b monolithic, silicon, quad darlington switch, linear microcircuit. |
| Test Data Document: |
| -mil-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0