

View Online at <https://aerobasegroup.com/nsn/5962-01-527-7732>

Body Length:

Between 0.337 inches and 0.344 inches

Body Width:

Between 0.150 inches and 0.157 inches

Body Height:

Between 0.043 inches and 0.065 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Avionics, c-17a aircraft

Features Provided:

Electrostatic sensitive and high speed and fail safe preconditioned

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Bipolar metal-oxide semiconductor

Design Function And Quantity:

1 transceiver, line differential

Current Rating Per Characteristic:

1.00 milliamperes reverse current, dc absolute

Product Name:

Microcircuit, digital, high speed rs-485/rs-422 transceiver, plastic encpsulated surface mount

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Special Test Features:

Upscreening testing consisting of extended temperature range testing of pem to -55 to +125 degrees celsius

Test Data Document:

89954-356a1409 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 89954-35a1407 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 gullwing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0