NSN 5962-01-531-1579

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-531-1579 **Body Length:** 1.415 inches **Body Width:** 0.605 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 790.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius **End Application:** F-15 avionics **Features Provided:** Hermetically sealed and burn in and w/buffered output and w/enable and high speed and ultraviolet erasable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital - cmos eprom msb

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Time Rating Per Chacteristic:

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Eprom

Memory Capacity:

65536 bit 8192 word

Special Features:

Program to cage 07187 truth table tt8513345-110

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

NSN 5962-01-531-1579

Memory Microcircuit - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0