NSN 5962-01-531-1730

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-531-1730

| Body Length: |
|--|
| Between 0.490 inches and 0.540 inches |
| Body Width: |
| Between 0.245 inches and 0.300 inches |
| Body Height: |
| Between 0.045 inches and 0.090 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| F-15 avionics |
| Features Provided: |
| Hermetically sealed and 3-state output and w/clock and programmable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 16 input |
| Design Function And Quantity: |
| 4 array, logic |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Microcircuit, digital - octal 16 input registered and- or, pal |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Memory Capacity: |
| Digital- octal 16 input |
| Special Features: |
| Program part 6135252-1 using cage 03640 tape number 6962598-13-010 |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 20 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5962-01-531-1730

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0