NSN 5962-01-531-3928

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-531-3928

Dedutemethy
Body Length:
0.440 inches
Body Width:
0.285 inches
Body Height:
0.085 inches
Maximum Power Dissipation Rating: 633.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application: Fwd fuselag f-15 aircraft
Features Provided:
Electrostatic sensitive and 3-state output and programmed
Inclosure Material:
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, memory32 x 8 bit prom
Voltage Rating And Type Per Characteristic:
7.0 volts total supply
Memory Device Type:
Prom
Memory Capacity:
32 x8 bit
Special Features:
Program from pn 6133740-2 cage 03640 or 5962-8670301fa per drawing 6133740 cage 03640
Test Data Document:
03640-6135494 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:

Terminal Type And Quantity:

16 flat leads

NSN 5962-01-531-3928

Memory Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

