## NSN 5962-01-531-4608

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-531-4608 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Fwd fuselag f-15 aircraft **Features Provided:** Hermetically sealed and burn in and monolithic and high speed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 2 channel and 10 input **Design Function And Quantity:** 4 selector, data, multiplexer, two to one line **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital cmos, se; ector/mutiplexer, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source **Memory Capacity:** None **Test Data Document:** 07148-83709 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit

N/a

Shelf Life:

## NSN 5962-01-531-4608

Digital Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0