NSN 5962-01-537-5533

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-537-5533

Body	Length:
------	---------

1.280 inches

Body Width:

Between 0.140 inches and 0.185 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

1.2 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Kc-135

Features Provided:

Electrostatic sensitive and programmed

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

22 input

Current Rating Per Characteristic:

16.00 milliamperes reverse current, dc

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, programmable array logic (pal) programmed, channel fail and clock driver

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 10.00 output picofarads

Time Rating Per Chacteristic:

15.00 nanoseconds input to output access

Memory Device Type:

Pal

Special Features:

Made from unprogramed microcircuit 5962-8867005la cage 67268

Terminal Type And Quantity:

24 printed circuit

NSN 5962-01-537-5533

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0