NSN 5962-01-540-3769

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-540-3769 |
|---|
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 300.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Electrostatic sensitive and monolithic and hermetically sealed and selected item and bipolar |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Operational amplifiers (integrated circuits) |
| Voltage Rating And Type Per Characteristic: |
| -18.0 volts power source and 18.0 volts power source and -10.0 volts input and 10.0 volts input |
| Special Features: |
| This item is selected from pn 1709/bgajc and screened by cage 31435 |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A 450-0 |

A458a0