NSN 5962-01-545-4086

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-545-4086 **Body Length:** 1.270 inches **Body Width:** 1.270 inches **Body Height:** 0.175 inches **Maximum Power Dissipation Rating:** 3.8 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Used on ug3500te01 cage 94580, electronic test station, ground support equipment for f-15 aircraft **Features Provided:** Low power and w/strobe and electrostatic sensitive **Inclosure Material:** Metal and ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 1 channel **Design Function And Quantity:** 1 driver and 1 receiver **Current Rating Per Characteristic:** 300.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Terminal Surface Treatment:** Solder **Product Name:** Hybrid, lower power driver/receiver for macair h009 specification Voltage Rating And Type Per Characteristic: 18.0 volts total supply **Hybrid Technology Type:** Monolithic **Terminal Type And Quantity:** 24 pin Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-545-4086

Hybrid Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0