## NSN 5962-01-545-9699

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-545-9699

Maximum Power Dissipation Rating:
470.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Analog card e/s; mcm 9-14 aft deck equipment
Features Provided:
Monolithic
Inclosure Material:
Silicon
Inclosure Configuration:
Leadless flat pack
Design Function And Quantity:
1 multiplexer, analog
Current Rating Per Characteristic:
20.00 milliamperes forward current, nonrepetitive, peak total value microamperes
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
44.0 volts total supply
Capitance Rating Per Characteristic:
8.00 input picofarads
Special Features:
Dual 4 channel analog multiplexer; dual in-line terminals; outline: gdip-1-t18 or cdip2-t18
Terminal Type And Quantity:
18 pin
Specification Data:
67268-5962-90635 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0