NSN 5962-01-549-5166

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-549-5166
Body Length:
1.060 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
0.6 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Pn a05g0600-2 test station electronic systems nsn 4920-01-420-5978 e/i f-15 aircraft.
Features Provided:
Electrostatic sensitive and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
1 latch, d
Current Rating Per Characteristic:
25.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable and 75.00 milliamperes reverse current, dc
absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, digital, advanced high speed cmos, octal transparent d-type latch with 3-state ouputs, monolithic silicon
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source and -0.5 volts input and 7.0 volts input
Capitance Rating Per Characteristic:
10.00 input picofarads and 10.00 output picofarads
Memory Capacity:
None
Terminal Type And Quantity:
20 printed circuit
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-549-5166

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0