NSN 5962-01-567-1001

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-567-1001

Body Length: 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 440.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+165.0 degrees celsius **End Application:** An/upm-155 iff test set aboard navy ships **Features Provided:** Hermetically sealed and monolithic and burn in and positive outputs **Inclosure Material:** Ceramic Inclosure Configuration: Dual-in-line **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 multivibrator, monostable **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 15.00 milliamperes reverse current, dc absolute Voltage Rating And Type Per Characteristic: 8.0 volts power source **Time Rating Per Chacteristic:** 7.00 nanoseconds propagation delay time, high to low level output and 7.00 nanoseconds propagation delay time, low to high level output **Memory Capacity:** Not rated **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a Unit Of Measure:

NSN 5962-01-567-1001

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

