NSN 5962-01-573-9840

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-573-9840

Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Aircraft, b-1b Inclosure Material: Siliicon Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig: A45830 Mil-std (military Standard): Mil-prf-38535 spec.	
End Application: Aircraft, b-1b Inclosure Material: Silicon Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Operating Tempurature Range:
Aircraft, b-1b Inclosure Material: Silicon Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	-55.0/+125.0 degrees celsius
Inclosure Material: Silicon Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	End Application:
Silicon Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Aircraft, b-1b
Inclosure Configuration: Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Notitize Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Inclosure Material:
Dual-in-line Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig: A458a0 Mil-std (military Standard):	Silicon
Output Logic Form: Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Inclosure Configuration:
Bipolar metal-oxide semiconductor Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Dual-in-line
Design Function And Quantity: 1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Output Logic Form:
1 counter, up/down, binary or decade Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Bipolar metal-oxide semiconductor
Product Name: Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Design Function And Quantity:
Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	1 counter, up/down, binary or decade
Voltage Rating And Type Per Characteristic: -0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Product Name:
-0.5 volts total supply and 7.0 volts total supply Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Microcircuit, digital, low-power schottky ttl, synchronous 4-bit up/down binary counter, monolithic silicon
Test Data Document: 96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Voltage Rating And Type Per Characteristic:
96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	-0.5 volts total supply and 7.0 volts total supply
Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Test Data Document:
16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	96906-mil-prf-38535 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	16 pin
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	N/a
Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	Unit Of Measure:
Yes - demil/mli Fiig: A458a0 Mil-std (military Standard):	
Fiig: A458a0 Mil-std (military Standard):	Demilitarization:
A458a0 Mil-std (military Standard):	Yes - demil/mli
Mil-std (military Standard):	Fiig:
	A458a0
Mil-prf-38535 spec.	Mil-std (military Standard):
	Mil-prf-38535 spec.