## NSN 5962-01-604-6276

Memory Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-01-604-6276
Overall Length:
Between 0.860 inches and 1.160 inches
Overall Width:
Between 0.610 inches and 0.790 inches
Body Length:
Between 0.360 inches and 0.420 inches
Body Width:
Between 0.860 inches and 1.160 inches
Body Height:
Between 0.045 inches and 0.090 inches
Maximum Power Dissipation Rating:
495.0 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Inclosure Configuration:
Leaded chip carrier
Output Logic Form:
Transistor-transistor logic
Voltage Rating And Type Per Characteristic:
-0.5 volts input and 7.0 volts input
Time Rating Per Chacteristic:
15.0 nanoseconds access
Memory Device Type:
Prom
Memory Capacity:
M1024
Test Data Document:
81349-mil38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
24 flat leads
Specification Data:
81349-mil-m-38510/231 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>

Fiig: A458a0

Demilitarization: Yes - demil/mli