NSN 5962-01-610-2151

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-610-2151

View Online at https://aerobasegroup.com/nsn/5962-01-610-2151
Overall Width:
Between 5.8 millimeters and 6.2 millimeters
Body Length:
Between 9.8 millimeters and 10.0 millimeters
Body Width:
Between 3.8 millimeters and 4.0 millimeters
Body Height:
Between 1.3 millimeters and 1.8 millimeters
Maximum Power Dissipation Rating:
1088.0 watts
Operating Tempurature Range:
-40.0 to 85.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
End Application:
Ghawk asip
Features Provided:
Low voltage
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
4 driver, line differential
Case Outline Source And Designator:
Mo-16a joint electron device engineering council
Terminal Surface Treatment:
Solder
Product Name:
3v lvds quad differential line driver
Voltage Rating And Type Per Characteristic:
-0.3 volts input and 4.0 volts input
Special Features:
Green (rohs and no sb/br) pkg- thin very small-outline package (tvsop)
Terminal Type And Quantity:
16 gullwing
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-610-2151

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0