## NSN 5962-01-624-7118

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-624-7118 liiheight: 1.2 millimeters **Body Length:** Between 4.9 millimeters and 5.1 millimeters **Body Width:** Between 4.3 millimeters and 4.5 millimeters **Operating Tempurature Range:** -40.0 to 85.0 degrees celsius **End Application:** 4920-01-495-9100 test station f16-c/d **Features Provided:** Electrostatic sensitive **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, logic **Current Rating Per Characteristic:** 50.0 milliamperes supply **Product Name:** Quadruple 2-input positive-and gates **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 9.00 nanoseconds propagation delay **Special Features:** Inputs are ttl-voltage compatible **Supplementary Features:** Tube pkg. Top side marking acht08 **Terminal Type And Quantity:** 

## 14 gullwing Shelf Life: N/a **Unit Of Measure:**

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-624-7118

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0