

View Online at <https://aerobasegroup.com/nsn/5962-01-643-2070>

**liilength:**

3.90 millimeters

**liiheight:**

0.80 millimeters

**liiwidth:**

3.90 millimeters

**Maximum Power Dissipation Rating:**

0.75 watts

**Operating Temperature Range:**

-40.0 to 85.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

W/field effect transistor switch and electrostatic sensitive

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Leadless flat pack

**Design Function And Quantity:**

1 switch, single pole double throw

**Terminal Surface Treatment:**

Tin and solder

**Product Name:**

High isolation spdt non-reflective switch

**Voltage Rating And Type Per Characteristic:**

7.0 volts total supply

**Special Features:**

Esd sensitivity is class 1a; dc blocking capacitors are required at ports rfc, rf1 and rf2; an enable input (en) set to logic high will put the switch in an "all off" state; leadframe material is copper alloy

**Terminal Type And Quantity:**

16 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0