

View Online at <https://aerobasegroup.com/nsn/5962-01-651-0265>

**liiheight:**

Between 0.90 millimeters and 1.45 millimeters

**liiwidth:**

Between 2.60 millimeters and 3.00 millimeters

**Body Length:**

Between 2.80 millimeters and 3.00 millimeters

**Body Width:**

Between 1.50 millimeters and 1.75 millimeters

**Maximum Power Dissipation Rating:**

696.0 milliwatts

**Operating Temperature Range:**

-40.0 to 85.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**End Application:**

V-22 aircraft

**Inclosure Configuration:**

Flat pack

**Design Function And Quantity:**

3 monitor, voltage

**Current Rating Per Characteristic:**

14.0 microamperes supply

**Product Name:**

Dual/triple ultra-low-voltage sot23 supervisory circuit

**Microcircuit Device Type And Quantity:**

1 linear

**Voltage Rating And Type Per Characteristic:**

0.8 volts total supply and 5.5 volts total supply

**Special Features:**

Reset threshold for primary supply is 3.00v to 3.150v and secondary supply is

**Terminal Type And Quantity:**

6 gullwing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A458a0