

View Online at <https://aerobasegroup.com/nsn/5962-01-651-0265>

liiheight:

Between 0.90 millimeters and 1.45 millimeters

liiwidth:

Between 2.60 millimeters and 3.00 millimeters

Body Length:

Between 2.80 millimeters and 3.00 millimeters

Body Width:

Between 1.50 millimeters and 1.75 millimeters

Maximum Power Dissipation Rating:

696.0 milliwatts

Operating Temperature Range:

-40.0 to 85.0 degrees celsius

Storage Temperature Range:

-65.0 to 150.0 degrees celsius

End Application:

V-22 aircraft

Inclosure Configuration:

Flat pack

Design Function And Quantity:

3 monitor, voltage

Current Rating Per Characteristic:

14.0 microamperes supply

Product Name:

Dual/triple ultra-low-voltage sot23 supervisory circuit

Microcircuit Device Type And Quantity:

1 linear

Voltage Rating And Type Per Characteristic:

0.8 volts total supply and 5.5 volts total supply

Special Features:

Reset threshold for primary supply is 3.00v to 3.150v and secondary supply is

Terminal Type And Quantity:

6 gullwing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0