## NSN 5962-01-651-1472

Microcircuit Assembly - Page 1 of 2



472

View Online at https://aerobasegroup.com/nsn/5962-01-651-1	
liiheight:	
Between 0.039 inches and 0.047 inches	
liiwidth:	
Between 0.462 inches and 0.470 inches	
Body Length:	
Between 0.721 inches and 0.729 inches	
Body Width:	
Between 0.396 inches and 0.404 inches	
Maximum Power Dissipation Rating:	
1.0 watts	
Operating Tempurature Range:	
-40.0 to 85.0 degrees celsius	
Storage Tempurature Range:	
-65.0 to 150.0 degrees celsius	
End Application:	
V-22 aircraft	
Inclosure Configuration:	
Dual-in-line	
Design Function And Quantity:	
1 memory, static ram	
Current Rating Per Characteristic:	
15.0 milliamperes output	
Product Name:	
4-mbit (512 k x 8/256 k x 16) nvsram	
Microcircuit Device Type And Quantity:	
1 memory	
Voltage Rating And Type Per Characteristic:	
2.70 volts input and 3.60 volts input	
Capitance Rating Per Characteristic:	
Between 61.0 input microfarads and 180.0 input microfarads	
Time Rating Per Chacteristic:	
25.0 nanoseconds read-write cycle	
Memory Device Type:	
Ram	
Memory Capacity:	
256k	
Terminal Type And Quantity:	
44 gullwing	
Shelf Life:	
N/a	

**Unit Of Measure:** 

## NSN 5962-01-651-1472

Microcircuit Assembly - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0