NSN 5962-01-651-1509

Microcircuit Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-651-1509

liiheight:

Between 0.095 inches and 0.110 inches

liiwidth:

Between 0.395 inches and 0.420 inches

Body Length:

Between 0.620 inches and 0.630 inches

Body Width:

Between 0.292 inches and 0.299 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-40.0 to 85.0 degrees celsius

Storage Tempurature Range:

-65.0 to 150.0 degrees celsius

End Application:

V-22 aircraft

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

1 memory, static ram

Current Rating Per Characteristic:

15.0 milliamperes output

Product Name:

1-mbit (128 k x 8/64 k x 16) nvsram

Microcircuit Device Type And Quantity:

1 memory

Voltage Rating And Type Per Characteristic:

2.7 volts input and 3.6 volts input

Capitance Rating Per Characteristic:

Between 61.0 input microfarads and 180.0 input microfarads

Time Rating Per Chacteristic:

25.0 nanoseconds read-write cycle

Memory Device Type:

Ram

Memory Capacity:

128k

Special Features:

Pb free

Terminal Type And Quantity:

48 gullwing

Shelf Life:

N/a

NSN 5962-01-651-1509

Microcircuit Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0