NSN 5963-00-007-5355

Overall Length: 2.620 inches

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-00-007-5355

| Overall Height: |
|--|
| 1.950 inches |
| Overall Width: |
| 0.590 inches |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 150.0 kilohertz operating channel |
| Pulse Duration Per Channel: |
| 800.000 milliseconds 2nd input channel err-100 |
| |
| Pulse Rise Time Per Channel: |
| Pulse Rise Time Per Channel: 0.100 microseconds 1st input channel err-100 |
| |
| 0.100 microseconds 1st input channel err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 Connection Type And Location: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 Connection Type And Location: Connector, plug bottom |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 Connection Type And Location: Connector, plug bottom Connector, plug external |
| 0.100 microseconds 1st input channel err-100 Pulse Decay Time Per Channel: 0.100 microseconds 2nd input channel err-100 Polarity Per Channel: Positive 1st operating channel err-100 Pulse Repetition Rate Per Channel: 800.000 kilopulses per second 2nd input channel err-100 Pulse Peak Amplitude Per Channel: 22.000 volts 2nd input channel err-100 Signal Data Type Per Channel: 2nd input channel pulse err-100 Connection Type And Location: Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: |

NSN 5963-00-007-5355

Standardized Electronic Module - Page 2 of 2



Test Data Document:

10001-2832000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

| Гуре/model | Designation: |
|------------|--------------|
|------------|--------------|

Rdq

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32200