

View Online at <https://aerobasegroup.com/nsn/5963-00-163-1573>

Overall Length:

7.820 inches

Overall Height:

2.500 inches

Overall Width:

3.000 inches

Vibration Resistance Range In Hertz:

+5.0 to 55.0

Vibration Resistance Amplitude:

0.06 inches total excursion

Shock Resistance Rating In Gravitational Units:

20.0

Operating Temperature Range:

+0.0 to 85.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encased

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Frequency Per Channel:

55.005 megahertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

10.0 milliwatts output

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms output channel

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, power rear and receptacle, coaxial top

Connection Contact Type And Quantity:

1 receptacle, coaxial internal and 9 receptacle, power external

External Dc Operating Voltage In Volts:

28.0 single voltage

Fsc Application Data:

Signal generator, test central, airborne weapon system, automatic

Reference Number Differentiating Characteristics:

As differentiated by the source control dwg no.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200