NSN 5963-00-173-2687

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-00-173-2687 **Overall Length:** 6.237 inches **Overall Height:** 2.062 inches **Overall Width:** 3.000 inches **Environmental Protection:** Fungus proof and moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +5.0 to 25.0 **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** +0.0 to 70.0 degrees celsius **Average Life Rating:** 10000.0 **Average Life Measurement:** Hours **Average Life Rating In Hours:** 10000.0 **Basic Shape Style:** Irregular **Identification Designator:** Fe-20-n0-hf1-14844 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Manual **Installation Design:** Module **Control Type:** Local **Circuit Construction Type:** Solid state **Frequency Per Channel:** 32.8 megahertz output channel **Attenuation In Decibels: Average Power Rating Per Channel:**

Not rated

NSN 5963-00-173-2687

Noncrystal Controlled Oscillator - Page 2 of 2



Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms output channel
Distortion Type And Percent:
5.0 phase
Indicator Device Type And Quantity:
1 meter
Maximum Continuous Operating Time In Hours:
10000.0
Connection Type And Location:
Single panel jack left side
External Dc Operating Voltage In Volts:
28.0 single voltage
Special Features:
Screwdriver output power adjustment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200