NSN 5963-00-194-9658

185.0 watts input

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5963-00-194-9658



Overall Length: 21.500 inches **Overall Height:** 13.000 inches **Overall Width:** 16.875 inches **Environmental Protection:** Moisture proof **Vibration Resistance Range In Hertz:** +10.0 to 55.0 **Individual Section Quantity: Operating Tempurature Range:** -40.0 to 131.0 degrees fahrenheit **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 0-39atra7-80058 **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Free-standing **Control Type:** Local **Circuit Construction Type:** Electron tube Frequency Shift: 850.0 hertz Frequency Per Channel: Frequency Adjustment Type: Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:**

NSN 5963-00-194-9658

Crystal Controlled Oscillator - Page 2 of 2



Signal Voltage Rating Per Channel:
44.000 volts output
Overall Gain:
Not rated
Impedance Rating Per Channel:
33.000 kilohms output channel
Distortion Type And Percent:
5.0 phase
Indicator Device Type And Quantity:
1 headset and 3 light
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Single panel jack front and receptacle, power front
Operating Ac Frequency In Hertz:
50.0 single voltage and 60.0 single voltage
External Ac Operating Voltage In Volts:
115.0 single voltage
Phase:
Single
Fsc Application Data:
Radio teletypewriter set group for radio set anmrc2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200