Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-00-337-0472

Overall Length:
1.400 inches
Overall Height:
0.875 inches
Overall Width:
0.900 inches
Environmental Protection:
Moisture proof
Operating Tempurature Range:
-55.0 to 95.0 degrees celsius
Average Life Rating:
454545.4
Average Life Measurement:
Hours
Average Life Rating In Hours:
454545.4
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
70000.0 feet
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Shift:
266.6 hertz
Frequency Per Channel:
13.3 megahertz operating channel
Signal Voltage Rating Per Channel:
3.000 volts output
Impedance Rating Per Channel:
700.000 ohms output channel err-100
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
4 printed circuit external
External Dc Operating Voltage In Volts:
5.2 single voltage

## NSN 5963-00-337-0472

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200