

NSN 5963-00-337-0780 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5963-00-337-0780 **Overall Length:** 2.000 inches **Overall Height:** 0.750 inches **Overall Width:** 2.000 inches **Environmental Protection:** Fungus proof and moisture proof **Vibration Resistance Range In Hertz:** +5.0 to 2000.0 **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 40.0 **Operating Tempurature Range:** -40.0 to 71.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 30000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Circuit Construction Type:**

Solid state

Frequency Per Channel:

727.0 hertz operating channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

5.000 volts output

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

NSN 5963-00-337-0780 Crystal Controlled Oscillator - Page 2 of 2



Indicator Device Type And Quantity:
Any acceptable
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
4 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Fsc Application Data:
Receiving set, countermeasures
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32200